

gl^t LED TUBE 150 D 5K++



Application area, Product advantages & Sustainability

Areas of Application

For all industrial sectors such as production, logistics and warehouse halls, exhibition halls.
Public buildings, offices, parking garages, parking facilities, wholesale markets.



Product Advantages GLT LED TUBE

- Double-ended LED lamp according to IEC EN 62776 for standard luminaires and fixtures (CE).
- Up to 80% energy savings.
- Lowest CO₂ carbon footprint on the market, reducing CO₂ emissions by 75%.
- Long lifetime 130,000 hours (L70 including power supply).
- High-performance power supply and surge protection integrated.
- AC/DC compatible: 185–265 V.
- Available as purchase, lease or rental.

Standard-compliant (CE), double-ended LED retrofit lamp for luminaires with conventional control gear (CCG/VVG). Starter is replaced by dummy and connected directly to 230 V.


Standard-compliant (CE), double-ended LED conversion lamp for luminaires with electronic control gear (EVG). Connected directly to 230 V by qualified electrician.

Sustainability

- Environmental Product Declaration (EPD) according to ISO 14025 and EN 15804 (Fraunhofer).
- Made in Germany – development and production exclusively in Germany.
- All components are replaceable and repairable.
- GLT reusable system – we take back used GLT LED TUBES.

Item No.	1001150550203003
EAN/GTIN	4262494090585
Certification	CE, ENEC 05 DEKRA, EPD
Photobiological protection class	0
IK protection rating	10
Ambient temperature	-40°C - +70°C
Switching cycles	>1.000.000
Warranty (years)	5
Base/socket	G13/T8
Cover	Diffuse
Length	150 cm
Dimensions	151,3 cm x 2,8 cm Ø
Net weight	427 g
Beam angle	150°
Luminous flux (lumens)	2.800 lm
Color temperature	5.000K
Color rendering index	Ra 92 - 94
L70 (70% luminous intensity)	L70 = 130.000 h
Input voltage	230 V
AC/DC compatible	185 V - 265 V
Power	17 W
Power supply integrated	High-Power-Supply
Operating frequency	50 - 60 Hz
Lifespan	>50.000 h
Power factor	>95
Energy consumption	16,8 kWh/1.000 h
Energy efficiency class	B
Customs tariff No.	85395200
Eprel	1386021

Light distribution



Light spectrum



All item no. are available with an adjustable end cap from 0° to 90°. Technical specifications remain unchanged.

The GLT LED TUBE complies with the essential requirements of the applicable EU directives and the Product Safety Act and bears the CE marking. When using the GLT LED TUBE in chemically aggressive ambient atmospheres, at elevated ambient temperatures, or in conditions of high or condensing humidity, please consult your advisor.