

®gtl® FIXE TRF trunking system



Areas of application

GLT FIXE trunking system for 1 - 2 GLT TUBES:

- Industrial areas, for example production- and logistic halls, warehouses, trade centers
- Offices, schools, hotels
- Parking garages
- Public buildings, wholesale stores

Product benefits

- Quick-mount trunking system for GLT TUBES without ballast
- Suitable for standard LED tubes according to EN 62776
- Lightweight and slim aluminium profile forms a single unit with the GLT TUBE
- Non-louvered, optionally with or without through-wiring
- Up to 80% energy savings with the GLT TUBE



article-nr.	description
1701153100000005	GLT FIXE TRF luminaire insert for 1 x GLT LED TUBE 1500 mm DV*
1701153100000007	GLT FIXE TRF luminaire insert for 1 x GLT LED TUBE 1500 mm EM*
1701153200000005	GLT FIXE TRF luminaire insert for 2 x GLT LED TUBE 1500 mm DV*
1701300000000022	GLT FIXE TRF luminaire insert for 2 x GLT LED TUBE 1500 mm EM*
1701020000000201	GLT FIXE TRF PVC cover 20 cm for feed-in
1701040000000200	GLT FIXE TRF PVC cover 40 cm for feed-in
1701142000000000	GLT FIXE TRF trunking empty model 142 DV*
1701000000000203	GLT FIXE TRF end cap white
1701000000001203	GLT FIXE TRF end cap white for feed-in
1701000000011203	GLT FIXE TRF 5+7-poles feed-in
1701300000000000	GLT FIXE TRF wire suspension 3 m
1701000000000100	GLT FIXE TRF trunking suspension bracket
1701000000000201	GLT FIXE TRF ceiling mounting bracket

*DV = luminaire with through wiring

*EM = housing usable as single luminaire or end module, without through-wiring.



Product data | GLT FIXE TRF trunking system

Certificates:	CE, Made in Germany	
IP protection class:	IP 20	
Operating temperature:	-40°C to +70°C	
Energy efficiency class:	A - B with GLT TUBE	
Warranty:	5 years	
Socket/base:	G13/T8	
Cover:	without cover	
Material:	aluminium white	
Net weight:	1,4 kg (1 x GLT TUBE) or 1,5 kg (2 x GLT TUBE)	
Length:	1545 mm	
Dimensions (L x B x H):	1 x GLT TUBE: 1545 x 655x 68 mm	2 x GLT TUBE: : 1545 x 102 x 75 mm
Through wiring (DV):	article-numbers 17011531000000005, 17011532000000005, 17011420000000000	
Packaging unit:	1 piece	

Electrical data


Input voltage:	230 Volt
Operating frequency:	50 Hz
Type of voltage:	AC
Type of connection:	7 poles plug-in
Lifetime:	>30 years

Mounting type: as continuous-row system
Mounting location: approved for indoor use only.

Accessories:



5+7-pole feed-in




ceiling mounting bracket



trunking suspension bracket



wire suspension 3 m



end cap white for feed-in



end cap white



PVC cover 20 cm for feed-in



PVC cover 40 cm for feed-in

The luminaire complies with the basic requirements of the applicable EU directives and product safety law and carries the CE mark. Please consult your consultant if the luminaire is to be used in chemically polluted environments, under increased ambient temperatures or high or condensing humidity.