



TUBE 85



Areas of application

High-End LED TUBE Made in Germany, sustainable and 90% recyclable:

- Industrial areas, for example production halls, warehouses, trade centers
- Offices, schools, hotels
- Wholesale stores, garages, public buildings



Product benefits

Highest quality and maximum energy saving:

- Double-capped LED retrofit lamp for suitable luminaires, fixtures and fittings according international norm IEC EN 62776.
- Up to 80% energy savings.
- Lowest CO₂ Carbon Footprint on the market, reduce of CO₂-output about 75%.
- Lifetime >50.000 hours.
- The high-performance power supply and overvoltage protection are integrated in the GLT TUBE.
- Samsung LEDs.
- CE conformity of the luminaire is maintained.
- Conversion possible as purchase, rental or leasing.



Double-capped LED conversion lamp that can be used as a replacement for another type of lamp that requires modification of the luminaire (ECG luminaire). In this case, the ballast is bridged by a qualified electrician using the GLT-conversion kit supplied.



Sustainability

GLT TUBES - resource-saving and economical:

- Environmental Product Declaration (EPD) in accordance with international standards ISO 14025 and EN 15804. Certified by the Institut Bauen und Umwelt e.V. as a LED light source for sustainable construction.
- Made in Germany -research, development and production exclusively in Germany.
- All components can be replaced and repaired.
- GLT reusable system - we take back your old GLT TUBES.



Product data | GLT TUBE 85

Certificates: CE, EPD
 Photobiological protection class: 0
 IK protection class: 10
 Operating temperature: -40°C to +70°C
 Switching cycles before failure: >1.000.000
 Warranty: 3 years

Socket/base: T5/G5
 Cover: Milky, Diffuse, Clear
 Length: 85 cm
 Weight: 264 g
 Dimensions: 85,7 cm x 2,8 cm Ø


Photometric characteristics

Beam angle: 90°, 120°, 150°
 Lumen: 1.500 lm - 2.100 lm
 Colour temperature: 3.000K, 4.000K, 5.000K
 Colour rendering index: Ra 92 - Ra 94
 L70 (70% luminous intensity): L70 = 130.000 hours


Electrical characteristics

Input voltage: 230 Volt
 Consumption: 14 W
 Power supply: Integrated high-performance power supply
 Operating frequency: 50 - 60 Hz
 Lifetime: >50.000 hours
 Power factor: >95
 Power consumption: 13,8 kWh/1.000 h


light distribution




light spectrum 3.000K



light spectrum 4.000K



light spectrum 5.000K



article-nr.	description	cover	colour temperature	luminous flux	EPREL-nr.	energy efficiency
1001850230202003	GLT TUBE 85 M 3K+	Milky 120°	3.000K	1.600 lm	1392530	AIG E
1001850240203003	GLT TUBE 85 M 4K++	Milky 120°	4.000K	2.100 lm	1392535	AIG C
1001850250203003	GLT TUBE 85 M 5K++	Milky 120°	5.000K	2.100 lm	1392540	AIG C
1001850530202003	GLT TUBE 85 D 3K+	Diffuse 150°	3.000K	1.500 lm		AIG E
1001850540203003	GLT TUBE 85 D 4K++	Diffuse 150°	4.000K	2.000 lm	1392549	AIG C
1001850550203003	GLT TUBE 85 D 5K++	Diffuse 150°	5.000K	2.000 lm	1903897	AIG C
1001850150203003	GLT TUBE 85 C 5K++	Clear 90°	5.000K	2.100 lm	1988153	AIG C

The luminaire complies with the basic requirements of the applicable EU directives and product safety law and carries the CE mark and EPD. Please consult your consultant if the luminaire is to be used in chemically polluted environments, under increased ambient temperatures or high or condensing humidity.